



25 BBL ELECTRIC BLENDING UNIT

▶ COMMON USES

The 25 bbl Electric Blending Unit is designed to mix mud for drilling operations. Also used for tank bottom reductions and tank cleaning for the industrial market.

▶ TECHNICAL DATA

DIMENSIONS		L X W X H	
EXTERNAL (MM)	3860 x 2438 x 2972		
EXTERNAL (FT)	12'8" x 8' x 9'9"		
WEIGHT		KGS	LBS
EMPTY WEIGHT	3538	7800	
CAPACITY		LITERS	GALS
VOLUME	3975	1050	
ADDITIONAL FEATURES			
FRAME			
<ul style="list-style-type: none"> • Designed for Offshore Dynamic Lifting in Accordance with API RR 2A • Steel Tubing Frame, Forklift Pockets on Both Sides, Built in Ladder, OSHA Compliant Hand Rails and Four Point Lift System • Work Platform For Easy Access to Palletized Material 			
VESSEL			
<ul style="list-style-type: none"> • Meets Class I DIV II Requirements • 10 HP Variable Speed Blender (up to 60 RPM) • 40 HP 4"x 5" Electric Centrifugal Pump • 4" Suction Line, 4" Fill Line, 4" Circulation Line and 3" Portable Tank Fill Line (Rota-Table) • Work Deck for Palletized Material with Swing Doors • Explosion-Proof Work Lights 			



▶ DRAWINGS

