



# 500 BBL CGA TRANSPORT TANK

## ▶ COMMON USES

The 500 bbl CGA Transport Tank provides secure transportation and storage of drilling, production and completion fluids as well as fuel, waste and other liquids.

## ▶ TECHNICAL DATA

DIMENSIONS	L X W X H	
EXTERNAL HAND RAILS DOWN (MM)	12649 x 3185 x 3607	
EXTERNAL HAND RAILS DOWN (FT)	41.5' x 10.5' x 12'	
EXTERNAL HAND RAILS UP (MM)	12649 x 3185 x 4422	
EXTERNAL HAND RAILS UP (FT)	41.5' x 10.5' x 14.5'	
WEIGHT	KGS	LBS
TARE	16783	37000
PAYLOAD	210013	463000
MAX GROSS WEIGHT (MGW)	226796	500000
CAPACITY	LITERS	GALS
VOLUME	79494	21000

### ADDITIONAL FEATURES

#### FRAME

- Designed for Offshore Dynamic Lifting in Accordance with API RP 2A & SEPCo OPS 0055
- Steel Frame, Two 20" Top Mounted Manways with Hand Rails, Ladder, Two Point Lift System (Empty Lift Only) & Eight Skid Mounted Weld Downs

#### VESSEL

- One 8" Suction/Drain with 6" Butterfly Valve with 4" Male Camlock & Cap or 4" fig. 206 hammer union
- One 4" Offset Circulation Line 4" with Butterfly Valve with 4" Female Camlock & Plug or 4" fig. 206 hammer union
- One 4" Fill Line with 4" Butterfly Valve with 4" Female Camlock & Plug or 4" fig. 206 hammer union
- One 30" Manway/Cleanout hatch
- One Maximum Working Pressure 18 PSI
- Optional additions: 3" Flame arrestor or 3" atmospheric vent
- Exterior Coating: Three Part Poly
- Interior Coating: High Build Chemical Resistant Liner



## ▶ DRAWINGS

